


## K.SR - Douilles 3/4" 12 pans métriques ADF



### Description :

- Alliage spécial Cuivre-Béryllium antidéflagrant et antimagnétique.

	A [mm]	Diamètre ré Maxi [mm]	longueur [mm]	Poids [g]
<b>K.17SR</b>	17.0	38.0	50.0	246.0
<b>K.19SR</b>	19.0	38.0	50.0	246.0
<b>K.21SR</b>	21.0	38.0	55.0	268.0
<b>K.22SR</b>	22.0	38.0	55.0	268.0
<b>K.23SR</b>	23.0	40.0	55.0	306.0
<b>K.24SR</b>	24.0	40.0	55.0	307.0
<b>K.26SR</b>	26.0	40.0	55.0	307.0
<b>K.27SR</b>	27.0	40.0	55.0	312.0
<b>K.28SR</b>	28.0	41.0	55.0	339.0
<b>K.29SR</b>	29.0	42.0	55.0	350.0
<b>K.30SR</b>	30.0	43.0	60.0	410.0
<b>K.32SR</b>	32.0	45.0	60.0	465.0
<b>K.34SR</b>	34.0	48.0	60.0	480.0
<b>K.36SR</b>	36.0	50.0	60.0	510.0
<b>K.38SR</b>	38.0	53.0	60.0	555.0
<b>K.41SR</b>	41.0	57.0	65.0	660.0
<b>K.46SR</b>	46.0	63.0	65.0	830.0
<b>K.50SR</b>	50.0	68.0	70.0	945.0